


Dual Frequency Access Door Reader

ISO14443A Mifare, EM125KHz compatible cards



- Multi RF card ISO14443A Mifare; EM125kHz EM410X or compatible
- **NXP** Original RF Chip with 128bit encryption
- Wall mount keypad form factors allow for US and EU compatible mounting options; creating a simpler install process at each door
- Tamper detection senses any type of altering and prevents a security breach with the device
- Total Flexibility – easily integrate with other systems or any third control system
- IP65 waterproof for indoor and outdoor harsh environment use
- Authorized certifications as CE, Rohs, CCC, FCC
- Firmware online upgrade
- OEM/ODM service
- One year-warranty

Applications

- Access Control
- Club / Loyalty System
- Parking system
- Printer Secure System
- E-payment, E-ticket



R280 is an economical access door reader with full-featured and fashion design for access control solution. Its efficient signalization system makes sure that the reader is easily seen. It is a dual frequency reader to support RF card as ISO14443A Mifare, EM125KHz, EM410X meeting different customer's requirement. What's more, original compact design provide ease of installation in various indoor and outdoor access applications.



Specifications

CREDENTIAL TYPES

ISO14443A Mifare Read/Write, EM125kHz Technology, EM410X or compatible

GENERAL INFO

R280E(EM125KHz), R280M(ISO14443A Mifare), R280EM(EM125KHz+ISO14443A Mifare)

5.2" x 2.4" x 0.9"(132mm x 62mm x 23mm)

Terminal Strip Installation

Card, PIN, Card+PIN Working Mode

POWER SUPPLY

9-24V DC

READING PERFORMANCE(Depending on antenna)

ISO14443A Mifare: >5CM

EM125KHz Card: >8CM

COMMUNICATION INTERFACES

RS232/RS485, Weigand26,34,40,42,50,56

ENVIRONMENTAL

IP65 Waterproof for indoor & outdoor

Operating Temperature -32° to 131° F (0° to 55° C)

Storage Temperature -4° to 140° F (-20° to 60° C)

Operating Humidity 5% to 95% relative humidity non-condensing

FCC Certification (US), CE (EU)

VISUAL INDICATOR

4x3 keypads with backlight, Doorbell

Buzzer and multi-color LED

SECURITY FEATURES

Tamper Detection

R280 series Order Guide

R280E-X	R280M-X	R280EM-X
R280E-X-K	R280M-X-K	R280EM-X-K

E: EM125kHz Technology, EM410X or compatible

M: ISO14443A Mifare Read/Write

K: With Keypad

X: X=2--> RS232 X=4---> RS485

XID reserves the right to change specification without notice at any time.

Date of publication: December 2017



5th Floor, Block I, Tongfuyu Industrial Park, Taoyuan Subdistrict, Nanshan District, Shenzhen, 518057, China

Tel: +86-75588226176 Fax: +86-755 88226177 Email: Sales@xid-tech.com